



LIQUID-APPLIED ROOF SOLUTIONS

Acrylic & Silicone Coatings Primers & Accessories

POLYGLASS®



PolyBrite® 70 Premium Grade Elastomeric Roof Coating



Features & Benefits

- ASTM D6083, Type I and Type II compliant
- Resistant to dirt pick up
- Fungal and algal resistant
- Resistant to ultraviolet energy
- Fire Retardant

Compatible Substrates

Mod Bit, SPUF, Most Metals, Concrete, Exterior Grade Plywood, Rigid Coverboards, Single Ply Membranes (Primer may be required)

Available Sizes

4.75 Gallon / 50 Gallon / Tote

Available Colors



Can be used to comply with 2016 Title 24 Part 6 Cool Roof Requirements (White Only)

PG 700 High Quality Elastomeric Roof Coating



Features & Benefits

- ASTM D6083, Type I and Type II compliant
- Resistant to dirt pick up
- Fungal and algal resistant
- Resistant to ultraviolet energy

Compatible Substrates

Mod Bit, Most Metals, Concrete, Exterior Grade Plywood, Rigid Coverboards, SPUF, Single Ply Membranes (Primer may be required)

Available Sizes

4.75 Gallon / 50 Gallon / Tote

Available Colors



Can be used to comply with 2016 Title 24 Part 6 Cool Roof Requirements (White Only)

PolyBrite® 75 High Tensile Premium Elastomeric Roof Coating



Features & Benefits

- ASTM D6083, Type I and Type II compliant
- Creates a tougher/stronger surface film
- Resistant to dirt pick up
- Fungal and algal resistant
- Resistant to ultraviolet energy
- Fire Retardant

Compatible Substrates

Mod Bit, SPUF, Most Metals, Concrete, Exterior Grade Plywood, Rigid Coverboards, Single Ply Membranes (Primer may be required)

Available Sizes

4.75 Gallon / 50 Gallon / Tote

Available Colors



Can be used to comply with 2016 Title 24 Part 6 Cool Roof Requirements (White Only)

PolyBrite® 71-HS Bleed Blocking Premium Elastomeric Roof Coating



Features & Benefits

- ASTM D6083, Type II compliant
- Bleed through resistance
- Resistant to dirt pick up
- Fungal and algal resistant
- Resistant to ultraviolet energy

Compatible Substrates

BUR, Granulated Mod Bit, Most Metals, Concrete, Exterior Grade Plywood, Rigid Coverboards, SPUF, Single Ply Membranes (Primer may be required)

Available Sizes

4.75 Gallon / 50 Gallon / Tote

Available Colors



Can be used to comply with 2016 Title 24 Part 6 Cool Roof Requirements (White Only)

PolyBrite® 55

Elastomeric Roof Coating for SPF



Features & Benefits

- Extends the useful life of the roof
- UV resistant
- Decreases roof surface temperature, which can reduce energy costs
- Resistant to dirt pick up
- Low VOC and non flammable

Compatible Substrates

Spray Polyurethane Foam



Available Sizes

4.75 Gallon / 50 Gallon

Available Colors



PolyBrite® 24

Elastomeric Roof Coating



Features & Benefits

- Resistant to dirt pick up
- Fungal and algal resistant
- Resistant to ultraviolet energy

Compatible Substrates

Mod Bit, SPUF, Most Metals, Concrete, Exterior Grade Plywood, Rigid Coverboards, Single Ply Membranes (Primer may be required)

Available Sizes

4.75 Gallon / 50 Gallon / Tote

Available Colors



Can be used to comply with 2016 Title 24 Part 6 Cool Roof Requirements (White Only)

PolyBrite® 76

Premium Elastomeric Base Coat



Features & Benefits

- Asphalt bleed through resistant
- Low permeability
- Fungal and algal resistant

Compatible Substrates

Mod Bit, Concrete and Other Masonry Surfaces

Available Sizes

4.75 Gallon / 50 Gallon



PolyBrite® 74

Rust Inhibitor



Features & Benefits

- Spot or field application
- Blue color to ensure full coverage
- Non-Flammable
- Cleans up easily with water

Compatible Substrates

Most Uncoated Metal Surfaces

Available Sizes

4.75 Gallon / 50 Gallon / Tote



PolyBrite® 71

Elastomeric Base Coat



Features & Benefits

- Flexible and durable
- UV resistant
- Resistant to asphalt staining and excellent 'bleed blocking' capabilities
- Will expand and contract with movement of roof surfaces
- Offer high tensile strength and elongation
- Low VOC and non-flammable
- Fungal and Algal resistant, even in high humidity environments
- Suitable for most surfaces and various roofing types

Compatible Substrates

Various conventional BUR, modified bitumen with smooth and mineral surfacing, most metal roofs, exterior grade plywood, Single-Ply membranes (primer may be required), rigid cover boards such as Dens-Deck® and Securock®, cementitious stucco and concrete materials. A substrate adhesion test is recommended prior to product application



Available Sizes

5 Gallon / 55 Gallon / Tote

Available Colors



PolyBrite® 31CB

Climate Barrier - High Temperature Elastomeric Protective Coating



Features & Benefits

- Easy application due to exceptional product flow
- Superior wet and dry hide
- Offers excellent resistance to extended exposure to solar ultraviolet energy
- By decreasing roof surface temperature, can reduce energy costs
- Good tensile strength and elongation
- Resistant to dirt pick-up
- Fungal and algal resistant
- Low VOC, non-flammable

Compatible Substrates

Various conventional smooth and granulated BUR and granulated polymer modified roof membranes, most metal roof systems, PVC single-ply membranes (Primer may be required), concrete, rigid coverboards such as Dens-Deck® and Securock®.

Available Sizes

5 Gallon / 55 Gallon / Tote

Available Colors



PolyBrite® 33 CS

Climate Shield - High Temperature Elastomeric Protective Coating



Features & Benefits

- Easy application due to exceptional product flow.
- Superior wet and dry hide
- Offers excellent resistance to extended exposure to solar ultraviolet energy
- UV resistant
- By decreasing roof surface temperature, can reduce energy costs
- Offers excellent tensile strength and elongation
- Fungal and algal resistant
- Low VOC, non-flammable

Compatible Substrates

Various conventional smooth and granulated BUR and polymer modified roof membranes with smooth mineral surfacing, most metal roof systems, single ply membranes (primers or special precautions may be required), concrete, exterior grade plywood, rigid coverboards such as Dens-Deck® and Securock® and SPUF. A substrate adhesion test is recommended prior to product application.



Available Sizes

5 Gallon / 55 Gallon / Tote

Available Colors



PolyBrite® 35 CA

Climate Armor - High Temperature Elastomeric Protective Coating



Features & Benefits

- Better hail resistance than typical elastomeric roof coatings
- Excellent toughness to foot traffic
- Easy application
- Superior wet and dry hide
- Offers excellent resistance to extended exposure to solar ultraviolet energy
- UV resistant
- By decreasing roof surface temperature, can reduce energy costs
- Offers high tensile strength and elongation
- Resistant to dirt pick up
- Fungal and algal resistant
- Low VOC, non-flammable

Compatible Substrates

Smooth and granulated BUR, SPUF, most metal roofs, modified bitumen membranes, concrete, exterior grade plywood rigid cover boards, and single-ply membranes. (May require a primer depending on age and condition.)



Available Sizes

5 Gallon / 55 Gallon / Tote

Available Colors



PolyBrite® 70-QS

Quick-Setting, Premium Grade Elastomeric Roof Coating



Features & Benefits

- ASTM D6083, Type I compliant
- Resistant to dirt pick up
- Fungal and algal resistant
- Resistant to ultraviolet energy
- Offers some resistance to early rainfall

Compatible Substrates

BUR, Granulated Mod Bit, SPUF, Most Metals, Concrete, Exterior Grade Plywood, Rigid Coverboards, Single Ply Membranes (Primer may be required)

Available Sizes

4.75 Gallon/50 Gallon/Tote

Available Colors



Can be used to comply with 2016 Title 24 Part 6 Cool Roof Requirements (White Only)

PG 700-QS

Quick-Setting, High Quality Elastomeric Roof Coating



Features & Benefits

- ASTM D6083, Type I compliant
- Resistant to dirt pick up
- Fungal and algal resistant
- Resistant to ultraviolet energy
- Offers some resistance to early rainfall

Compatible Substrates

Mod Bit, Most Metals, SPUF, Concrete, Exterior Grade Plywood, Rigid Coverboards, Single Ply Membranes (Primer may be required)

Available Sizes

4.75 Gallon/50 Gallon/Tote

Available Colors



Can be used to comply with 2016 Title 24 Part 6 Cool Roof Requirements (White Only)

PolyBrite® 90

High Solids Silicone Roof Coating



Features & Benefits

- ASTM D6694; C1305 compliant
- Not adversely affected by ponding water
- Fungal and algal resistant
- Incorporates fire retardant
- Resistant to ultraviolet energy
- Moisture Cure
- Greater DFT per gallon

Compatible Substrates

Mod Bit, SPUF, Most Metals, Concrete, Single Ply Membranes (Primer may be required)

Available Sizes

5 Gallon/50 Gallon

Available Colors



Can be used to comply with 2016 Title 24 Part 6 Cool Roof Requirements (White Only)

PolyBrite® 90.1

High Solids Silicone Roof Coating



Features & Benefits

- ASTM D6694; C1305 Compliant
- Not adversely affected by ponding water
- Fungal and algal resistant
- Incorporates fire retardant
- Resistant to ultraviolet energy
- Low VOC
- Moisture Cure
- Greater DFT per gallon

Compatible Substrates

Granulated Cap Sheets, Smooth BUR, SPUF, Most Metals, Concrete, Well Adhered Acrylic Coatings, Single Ply Membranes (Primer may be required)

Available Sizes

5 Gallon/55 Gallon

Available Colors



Can be used to comply with 2016 Title 24 Part 6 Cool Roof Requirements (White Only)

PolyBrite® 95 Silicone Roof Coating



Features & Benefits

- ASTM D6694; C1305 compliant
- Not adversely affected by ponding water
- Fungal and algal resistant
- Incorporates fire retardant
- Resistant to ultraviolet energy
- Moisture Cure
- Easy application
- Excellent sprayability

Compatible Substrates

Mod Bit, SPUF, Most Metals, Concrete, Single Ply Membranes (Primer may be required)

Available Sizes

5 Gallon / 50 Gallon

Available Colors



Can be used to comply with 2016 Title 24 Part 6 Cool Roof Requirements (White Only)

PolyBrite® 95.1 Silicone Roof Coating



Features & Benefits

- ASTM D6694 compliant
- Not adversely affected by ponding water
- Fungal and algal resistant
- Incorporates fire retardant
- Resistant to ultraviolet energy
- Moisture Cure
- Easy application
- Excellent sprayability

Compatible Substrates

Mod Bit, SPUF, Most Metals, Concrete, Well Adhered Acrylic Coatings, Single Ply Membranes (Primer may be required)

Available Sizes

5 Gallon / 50 Gallon

Available Colors



Can be used to comply with 2016 Title 24 Part 6 Cool Roof Requirements (White Only)

PolyBrite® 98 One-Part Acrylic Primer/Bleed Blocker for Silicone Coatings



Features & Benefits

- Versatile for a wide variety of substrates
- Low VOC
- Non-flammable
- Rain resistant after 3 hours

Compatible Substrates

Galvanized Steel, Aluminum, Granulated Mod Bit, Wood, Masonry

Available Sizes

5 Gallon / 55 Gallon



PolyBrite® 84 Rust Inhibitive Primer



Features & Benefits

- Inhibits further oxidation of metal roofs
- Can be used as both a spot rust primer and for application to widespread area of the roof
- Promotes adhesion of elastomeric coatings
- Compliant with VOC requirements <50 g/l
- Non-flammable

Compatible Substrates

Most Metal Roofs

Available Sizes

4.75 Gallon / 50 Gallon



PolyBrite® 745

Water-Based Primer/Adhesive



Features & Benefits

- For both horizontal and vertical surfaces
- Stain blocker
- Can be used to adhere reinforcement fabrics
- Ideal primer for use with Polyglass cap sheets

Compatible Substrates

Granulated Mod Bit, Masonry, Wood, Concrete, Previously Coated Surfaces

Available Sizes

4.75 Gallon / 50 Gallon / Tote



PolyBrite® 78

Rinseable EPDM Primer



Features & Benefits

- Low-viscosity sprayable liquid used to pre-treat EPDM
- Promotes adhesion of elastomeric coatings
- Neutral pH formula
- Non corrosive

Compatible Substrates

EPDM

Available Sizes

5 Gallon

PolyBrite® 780

Epoxy Primer/Sealer



Features & Benefits

- Increases the bond of acrylic elastomeric coatings and spray polyurethane foam SPUF to roof surface
- Maximizes radiant heat to maximize SPUF yield

Compatible Substrates

Mod Bit, BUR, Plywood, Concrete, Fiberglass, Most Metals, SPUF

Available Sizes

4.75 Gallon / 50 Gallon

WB 3000

Fast-Drying, Water-Based Primer



Features & Benefits

- One component, water-based acrylic primer
- Enhances adhesion of self-adhered membranes and acrylic coatings
- Quickly dried to tacky surface
- Low VOC

Compatible Substrates

Masonry, Metal, Asphalt, Wood, Plywood, Various Gypsum Boards

Available Sizes

5 Gallon



PolyBrite® 79 TPO/PVC Primer



Features & Benefits

- VOC compliant
- Single coat application
- One component
- Quick Drying

Compatible Substrates

Aged TPO & PVC

Available Sizes

4.75 Gallon/50 Gallon



PolyBrite® 97x Epoxy Primer



Features & Benefits

- Enhances adhesion of Polyglass silicone coatings to a variety of porous and non-porous substrates
- Alkali Resistance
- Low VOC
- Non-flammable
- Two component

Compatible Substrates

Mod Bit, Most Metals, Wood, Masonry

Available Sizes

5 Gallon



PG 800 Asphalt Emulsion Roof Coating



Features & Benefits

- ASTM D1227, Type III Class 1 compliant
- Highly flexible
- Exceptional weathering characteristics

Compatible Substrates

Smooth BUR, Mod Bit, Most Metals, Masonry, Stucco, Curbs & Base Flashings

Available Sizes

5 Gallon/55 Gallon/Tote



PolyFlash® 1C One Part Flashing Compound



Features & Benefits

- One-component
- High Tensile
- Crack Bridging
- UV resistant
- Use in combination with PolyBrite Reinforcing Polyester

Compatible Substrates

Conventional BUR, Mod Bit, Masonry, Wood, Gypsum Sheathing Products, Most Metals, EPDM

Available Sizes

1 Gallon/2.5 Gallon



PolyBrite® 73

Elastomeric Flashing Compound With StretchSpan Technology™



Features & Benefits

- Expands and contracts with the movement of the roof
- Provides a permanent waterproof seal at flashing details and fastener heads
- Flexible
- Strong
- Pliable

Compatible Substrates

Conventional BUR, Mod Bit, SPUF, Wood, Most Metals, Concrete

Available Sizes

1.8 Gallon / 4.75 Gallon

PolyBrite® 77

Premium Grade SEBS Cement



Features & Benefits

- Seals screw heads and fasteners and vertical seams on metal roofing
- Flexible
- Strong
- UV resistant

Compatible Substrates

Most Metals, Screw Heads, Fasteners, Concrete, Aged TPO and PVC

Available Sizes

3.5 Gallon



PolyBrite® 93

Silicone Flashing Compound



Features & Benefits

- Flexible
- Low odor
- Easy to apply
- VOC compliant
- Fast moisture-cure
- UV resistant
- Excellent resistance to weathering
- Superior adhesion to a variety of substrates
- Suitable for most surfaces and various roofing types
- Provides a permanent waterproof seal at flashing and penetrations

Compatible Substrates

Conventional BUR, smooth and granulated modified roof membranes (primer may be required), wood, concrete and most metal roofs

Available Sizes

2 Gallon

PolyBrite® 39

Elastomeric Flashing Compound



Features & Benefits

- Will expand and contract with movement of roof surfaces
- Provides a permanent waterproof seal at flashing details and fastener heads
- Suitable for most surfaces and various roofing types
- No migration of plasticizers and oils that inhibit adhesion and product performance

Compatible Substrates

Various conventional BUR, modified bitumen, metal, wood, spray polyurethane foam (SPF), single ply membranes (primer may be required) and concrete materials

Available Sizes

2 Gallon / 5 Gallon

Available Colors



PolyPUF™ Spray Polyurethane Foam Roof Insulation



Features & Benefits

- Seamless and self-flashing
- Eliminates thermal bridging
- Improves energy efficiency

Compatible Substrates

Most Construction Materials

Available Sizes

Refer to Product Data Sheet for product size availability



POLYSLOPE™ Reinforced Cementitious Compound



Features & Benefits

- Just add water and mix
- Easy screed
- Self-reinforcing
- Creates positive drainage

Compatible Substrates

Mod Bit, BUR, Plywood, Concrete, Single Ply

Available Sizes

50 lb. Pail

Polyglass Detail & Repair Finish Featuring CURE Technology®



Features & Benefits

- Reflective
- Enhances granule retention
- Improves abrasion and scuff resistance

Compatible Substrates

Polyfresko® Highly Reflective White Cap Sheet Membranes

Available Sizes

1 Gallon / 5 Gallon



PolyBrite® FMT Field Mix Thickener



Features & Benefits

- Modifies thickness to enhance sag resistance of silicone coatings
- For in field use
- Quick and easy to mix

Compatible For Use With

Silicone Coatings

Available Sizes

5 Gallon

Granules

Mineral Granules



Features & Benefits

- Weather resistant
- Non-porous
- Dense
- Available in a variety of colors

Available Sizes

50 Pound Pail

PolyBrite® Reinforcing Polyester

Reinforcing Polyester



Features & Benefits

- Used to reinforce cold process roofing systems
- Flexible
- Available in different sizes

Compatible For Use With

Acrylic Coatings
Silicone Coatings
Emulsion
PolyFlash 1C
PolyProof 1103

Available Sizes

6" x 300'
12" x 300'
40" x 324'

PolyClean™

Cleaning Concentrate



Features & Benefits

- Excellent with high or low pressure, hot or cold water
- Cleans mold and mildew, grease, AC fluid and other challenging contaminants

Compatible Substrates

Smooth or granule surface modified, built-up and previously coated roofing substrates, metal roofs, wall surfaces, concrete, as well as deck coatings for pedestrian and vehicular traffic

Available Sizes

1 Gallon/5 Gallon/55 Gallon



POLYGLASS®
MAPEI
GROUP



POLYGLASS U.S.A., Inc.

1111 West Newport Center Drive
Deerfield Beach, FL 33442
pgmarketing@polyglass.com
Customer Service: (800) 222-9782

polyglass.us

© 2023 Polyglass U.S.A., Inc. All rights reserved.

All information printed is accurate at the time of publication and may change at any time with or without notice.
For the most up to date information and data, please visit our website at polyglass.us.