




Atlas Nail Base Fastener

Nailable Insulation Fastener

DESCRIPTION: Standard or Light Duty insulation fastener with #2 Light Duty Drill Point. Specially engineered for attaching Atlas EnergyShield® Ply Pro to light steel and wood substrates.



- MATERIAL:** Case hardened and Tempered Carbon Steel
- HEAD STYLE/DRIVE:** Pancake Head with T-30 Internal Drive
- HEAD DIAMETER:** 0.625"
- SHANK DIAMETER:** 0.190"
- THREAD LENGTH:** 2.750"
- OVERALL LENGTH:** 3" thru 18"
- POINT:** #2 (0.135" dia.) Drill Point
- COATING:** Epoxy E-Coat (black)
- Passes more than 15 cycles (Kesternich) in accordance with DIN 50018*



PRODUCT SELECTION

IN	MM	PKG. QTY.
3.0	76	500/PAIL
3.5	89	500/PAIL
4.0	102	500/PAIL
4.5	114	500/PAIL
5.0	127	500/PAIL
5.5	140	500/PAIL
6.0	152	500/PAIL
6.5	165	500/PAIL
7.0	178	500/PAIL
7.5	191	500/PAIL
8.0	203	500/PAIL
8.5	216	250/PAIL
9.0	229	250/PAIL
10.0	254	250/PAIL
11.0	279	250/PAIL
12.0	305	250/PAIL
13.0	330	250/BOX
14.0	356	250/BOX
15.0	381	250/BOX
16.0	406	250/BOX
18.0	457	250/BOX

TENSILE STRENGTH	SHEAR STRENGTH	HEAD PULL-THRU VALUE (7/16" OSB)
3,380 lbf	2,900 lbf	545 lbf

LATERAL LOAD RESISTANCE ¹		
MAIN MEMBER	SIDE MEMBER	LOAD
22 Ga. Corrugated Steel	Nail Base	411 lbf
7/16" OSB	Nail Base	112 lbf

WITHDRAWAL VALUES IN STEEL ¹ (80 KSI MIN.)			
Type B Corrugated	22 Ga.	20 Ga.	18 Ga.
lbf	510	645	920

WITHDRAWAL VALUES IN WOOD ¹							
Specific Gravity	0.67	0.55	0.50	0.46	0.43	0.36	0.31
lb/in.	1429	1173	1067	981	917	768	661

¹Head Pull-Thru, "Withdrawal" and "Lateral Load" data reflect average ultimate values.

NOTE: Two T-30 Driver Bits included in each package.

T-30 DRIVER BIT



Note: All tests were conducted by an independent testing laboratory. Test results are offered only as a guide and are not guaranteed in any way by Atlas Roofing Corporation.

Other than the aforementioned representations and descriptions, Atlas Roofing Corporation (hereafter, "Seller") makes no other representations or warranties as to the insulation sold herein. The Seller disclaims all other warranties, express or implied, including the warranty of merchantability and the warranty of fitness for a particular purpose. Seller does, however, have a limited warranty as to the LTR-Value of the insulation, the terms of which are available upon request from the Seller. Seller shall not be liable for any incidental or consequential damages including but not limited to the cost of installation, removal, repair or replacement of this product. Buyer's remedies shall be limited exclusively to, at Seller's option, the repayment of the purchase price or resupply of product manufactured by Atlas in a quantity equal to that of the nonconforming product. Atlas distributors, agents, salespersons or other independent representatives have no authority to waive or alter the above limitation of liability and remedies.