

Prepared Roofing Accessories

COMPANY**R25992****Polyglass USA Inc**

1111 W NEWPORT CENTER DR

DEERFIELD BEACH, FL 33442 United States

*View model for additional information***Investigated to UL 790 and ULC 107****Asphalt Underlayment, [Eagle Anchor XFR](#)****Asphalt Underlayment, [PolyAnchor HV](#)****Asphalt Underlayment, [PolyAnchor UDL 40](#)****Asphalt Underlayment, [PolyAnchor XFR](#)****Asphalt Underlayment, [Polystick MTS](#)****Asphalt Underlayment, [Polystick MTS Plus](#)****Asphalt Underlayment, [Polystick MU-X](#)****Asphalt Underlayment, [Polystick MX](#)****Asphalt Underlayment, [Polystick P](#)****Asphalt Underlayment, [Polystick PX HT](#)****Asphalt Underlayment, [Polystick TU Plus](#)****Asphalt Underlayment, [Polystick XFR](#)****Asphalt Underlayment, [Polystick® IR-Xe](#)****Asphalt Underlayment, [PolyVap SA G](#)****Other, [Polystrip SA](#)****[Last Updated](#) on 2025-09-02**

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."

Model PolyAnchor HV

File Number: R25992

COMPANY

Polyglass USA Inc

1111 W NEWPORT CENTER DR
DEERFIELD BEACH, FL 33442 United States

MODEL INFO

PolyAnchor HV
Asphalt Underlayment

RESISTANCE TO EXTERNAL FIRE CERTIFICATION(S)

UL 790 (TGDY):

Classified

ULC 107 (TGDY7):

Classified

RESISTANCE TO EXTERNAL FIRE CERTIFICATION NOTES

Classification

Mechanically fastened modified bitumen membrane for use in the installation of Class A asphalt glass fiber mat shingles and Class C asphalt organic felt shingles.

MATERIAL SPECIFICATION CERTIFICATION(S)

ASTM D6757 (TGDY):

N/A

ASTM D226 (TGDY):

N/A

ASTM D4869 (TGDY):

N/A

ASTM D1970 (TGDY):

N/A

Report Date: 2023-08-29

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."

Model Polystick® IR-Xe

File Number: R25992

COMPANY

Polyglass USA Inc

1111 W NEWPORT CENTER DR
DEERFIELD BEACH, FL 33442 United States

MODEL INFO

Polystick® IR-Xe
Asphalt Underlayment

RESISTANCE TO EXTERNAL FIRE CERTIFICATION(S)

UL 790 (TGDY):

Classified

ULC 107 (TGDY7):

Classified

RESISTANCE TO EXTERNAL FIRE CERTIFICATION NOTES

Classification

Self-adhering, modified bitumen membranes for use in the installation of Class A asphalt glass fiber mat shingles and Class C asphalt organic felt shingles.

MATERIAL SPECIFICATION CERTIFICATION(S)

ASTM D6757 (TGDY):

N/A

ASTM D226 (TGDY):

N/A

ASTM D4869 (TGDY):

N/A

ASTM D1970 (TGDY):

N/A

Report Date: 2008-10-13

Revision Date: 2025-08-28

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."

Model Polystick PX HT

File Number: R25992

COMPANY

Polyglass USA Inc

1111 W NEWPORT CENTER DR

DEERFIELD BEACH, FL 33442 United States

MODEL INFO

Polystick PX HT

Asphalt Underlayment

RESISTANCE TO EXTERNAL FIRE CERTIFICATION(S)

UL 790 (TGDY):

Classified

ULC 107 (TGDY7):

Classified

RESISTANCE TO EXTERNAL FIRE CERTIFICATION NOTES

Classification

Self-adhered modified bitumen membrane for use in the installation of Class A asphalt glass fiber mat shingles and Class C asphalt organic felt shingles.

Report Date: 2025-08-07

Revision Date: 2025-08-21

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."

Model Polystick TU Plus

File Number: R25992

COMPANY

Polyglass USA Inc

1111 W NEWPORT CENTER DR
DEERFIELD BEACH, FL 33442 United States

MODEL INFO

Polystick TU Plus
Asphalt Underlayment

RESISTANCE TO EXTERNAL FIRE CERTIFICATION(S)

UL 790 (TGDY):

Classified

ULC 107 (TGDY7):

Classified

RESISTANCE TO EXTERNAL FIRE CERTIFICATION NOTES

Classification

Self-adhering, modified bitumen membranes for use in the installation of Class A asphalt glass fiber mat shingles and Class C asphalt organic felt shingles.

MATERIAL SPECIFICATION CERTIFICATION(S)

ASTM D6757 (TGDY):

N/A

ASTM D226 (TGDY):

N/A

ASTM D4869 (TGDY):

N/A

ASTM D1970 (TGDY):

N/A

Report Date: 2008-10-13

Revision Date: 2025-08-28

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."

Model Polystick MTS Plus

File Number: R25992

COMPANY

Polyglass USA Inc

1111 W NEWPORT CENTER DR

DEERFIELD BEACH, FL 33442 United States

MODEL INFO

Polystick MTS Plus

Asphalt Underlayment

RESISTANCE TO EXTERNAL FIRE CERTIFICATION(S)

UL 790 (TGDY):

Classified

ULC 107 (TGDY7):

Classified

RESISTANCE TO EXTERNAL FIRE CERTIFICATION NOTES

Classification

Self-adhering, modified bitumen membranes for use in the installation of Class A asphalt glass fiber mat shingles and Class C asphalt organic felt shingles.

MATERIAL SPECIFICATION CERTIFICATION(S)

ASTM D6757 (TGDY):

N/A

ASTM D226 (TGDY):

N/A

ASTM D4869 (TGDY):

N/A

ASTM DI970 (TGDY):

N/A

Report Date: 2008-10-13

Revision Date: 2025-08-28

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."

Model Polystick MX

File Number: R25992

COMPANY

Polyglass USA Inc

1111 W NEWPORT CENTER DR
DEERFIELD BEACH, FL 33442 United States

MODEL INFO

Polystick MX
Asphalt Underlayment

RESISTANCE TO EXTERNAL FIRE CERTIFICATION(S)

UL 790 (TGDY):

Classified

ULC 107 (TGDY7):

Classified

RESISTANCE TO EXTERNAL FIRE CERTIFICATION NOTES

Classification

Self-adhering, modified bitumen membranes for use in the installation of Class A asphalt glass fiber mat shingles and Class C asphalt organic felt shingles.

MATERIAL SPECIFICATION CERTIFICATION(S)

ASTM D6757 (TGDY):

N/A

ASTM D226 (TGDY):

N/A

ASTM D4869 (TGDY):

N/A

ASTM D1970 (TGDY):

N/A

Report Date: 2008-10-13

Revision Date: 2025-08-28

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."